

Manufacturer & Stockist of Heating, Ventilation & Air Movement Equipment

Units 2 & 3 Bull Ring Trading Estate, Green Street, Digbeth, Birmingham, B12 0NB. Tel: 0121 766 8126 Fax: 0121 766 7239 www.ajs-vent.co.uk



<u>GFLEX</u> GREY PVC FLEXIBLE DUCT

Technical Data

Size Range

- 80mm Ø to 610mm Ø.
- Length: 6m.
- Compressed Packaged Length: 800mm per Box.

Performance

- Temperature Range: -10°C to +75°C.
- Max Air velocity: 30m/sec.
- Max Positive Pressure: 3000Pa.

Material

 Double Laminate Reinforced with High Density Scrim (No Longer PVC Coated).

Description / Full Features:

AJS GFLEX is designed specifically for the HVAC Industry.

The range offers a quick and simplified solution for connecting to circular and oval ducting for normal ventilation and air conditioning purposes. A reinforced flexible duct that is suitable for high pressure, constant flexing and bending.

No longer PVC coated, but a double laminated reinforced with high density scrim.

AJS are proud to be associated with:







Every effort is made to ensure the information in AJS literature is correct, however no warranty is given in this respect and the company shall not be liable as a result of any inaccuracy. The company has a policy of continuous product development and reserves the right to alter, at any time, specification without prior notice